

***PUBLIC UTILITY DISTRICT NO. 1 OF WHATCOM COUNTY***  
***D STATION - FLOW AND CONTROL IMPROVEMENTS***

**BLAINE**

**DRAYTON HARBOR**

**BIRCH BAY**

**GRANDVIEW ROAD**

**ALDERGROVE RD.**

**KICKERVILLE ROAD**

**I-5**

**APPROXIMATE SCALE: 1" = 7,000'**

**BP CHERRY POINT  
REFINERY**

**ALDERGROVE ROAD**

**PROJECT LOCATION**


APPROXIMATE SCALE: 1" = 7,000'

IMAGE COURTESY OF GOOGLE EARTH 2015


<b><i>SHEET NUMBER</i></b>	<b><i>SHEET TITLE</i></b>	<b><i>DWG NO.</i></b>
1	COVER	COV
2	LEGEND AND GENERAL NOTES	G01
3	EXISTING SITE, DEMOLITION & TESC PLAN	C01
4	PHASING PLAN	C02
5	PROPOSED SITE PLAN	C03
6	SITE DETAILS I	C04
7	BUILDING ELEVATIONS	S01
8	STRUCTURAL DETAILS I	S02
9	STRUCTURAL DETAILS II	S03
10	MECHANICAL PLAN & SECTIONS	M01
11	D STATION MECHANICAL IMPROVEMENTS	M02
12	ELECTRICAL LEGEND	E01
13	ELECTRICAL SITE PLAN	E02
14	ELECTRICAL PLAN I	E03
15	ELECTRICAL PLAN II	E04
16	ELECTRICAL PLAN III	E05
17	ELECTRICAL PLAN IV	E06
18	ELECTRICAL SCHEDULES	E07
19	ELECTRICAL DETAILS	E08

**REPORT ALL SPILLS**  
**DEPT. OF ECOLOGY 1-800-258-5990**

CONTACT	AGENCY	PHONE
KURT WANK (PROJECT MANAGER)	WPUD	360.384.4288 ext 17
GARRETT LOVE-SMITH (PROJECT MANAGER)	WPUD	360.384.4288 est 26
ORIN PAUL, P.E. (PROJECT MANAGER)	RH2 ENGINEERING	360.684.1556
KAYLIE DENNEHY, E.I.T. (PROJECT ENGINEER)	RH2 ENGINEERING	360.684.1557
MARK BRAAKSMA (ELECTRICAL ENGINEER)	RH2 ENGINEERING	360.684.1552
KAYLEY HASKINS	OLYMPIC PIPELINE	360-399-8172
CAROL BIRD-TERRELL	BP CHERRY POINT	360-303-1471



**CIVIL/MECHANICAL**  
SIGNED: 04/13/2023



**CIVIL/MECHANICAL**  
SIGNED: 04/13/2023

























**ELECTRCAL**  
SIGNED: 04/13/2023



LEGEND	
--------	--

## EXISTING LEGEND

	BENCH MARK
	SET MAG NAIL/FLASHER
	EASEMENT
	PROPERTY LINE
	RIGHT OF WAY
	MAJOR CONTOUR
	MINOR CONTOUR
	UTILITY POLE
	POWER PAD MOUNT TRANSFORMER
	UNDERGROUND TELEPHONE
	UNDERGROUND POWER
	OVERHEAD POWER
	STORM DRAIN LINE
	WATERMAIN
	WATERMAIN STRUCTURE
	RAILROAD TRACK
	MONITORING WELL
	FENCE
	BUILDING EDGE
	ROADWAY ASPHALT AREA
	CONCRETE
	SURVEY FEATURE INDICATED ON PLAN

 GRAVEL REMOVAL

 UTILITY REMOVAL LIMITS

	BUILDING
	CRUSHED SURFACING TOP COURSE
	REVERSE THRUST BLOCK
	HORIZONTAL THRUST BLOCK
	WATER MAIN
	SUMP PUMP DISCHARGE PIPE
	CHAIN LINK FENCE
	TEE
	CROSS
	BEND
	REDUCER
	RESTRAINED JOINT
	VALVE

GENERAL NOTES	
---------------	--

1. A COPY OF THE APPROVED PLANS MUST BE ON-SITE WHENEVER CONSTRUCTION IS IN PROGRESS.

2. FORTY- EIGHT HOUR NOTICE WILL BE REQUIRED PRIOR TO STARTING NEW CONSTRUCTION AND THE CONTRACTOR MUST HOLD A PRECONSTRUCTION MEETING WITH THE OWNER PRIOR TO THE START OF CONSTRUCTION.
3. ALL WORKMANSHIP, CONSTRUCTION AND MATERIALS SHALL BE IN ACCORDANCE WITH THESE SPECIAL PROVISIONS, PLANS, WHATCOM COUNTY DEVELOPMENT STANDARDS (LATEST EDITION), AND THE 2023 EDITION OF THE WSDOT STANDARD SPECIFICATIONS FOR ROAD, BRIDGE, AND MUNICIPAL CONSTRUCTION, AS ISSUED BY THE WASHINGTON STATE DEPARTMENT OF TRANSPORTATION AND THE AMERICAN PUBLIC WORKS ASSOCIATION, WHICH IS HEREINAFTER REFERRED TO AS THE STANDARD SPECIFICATIONS.
4. CONSTRUCTION ACTIVITY SHALL OCCUR BETWEEN 7:00AM TO 8:00PM AND MAY BE MODIFIED AS NECESSARY TO COMPLETE THE CONSTRUCTION WITH WHATCOM COUNTY PUBLIC WORKS APPROVAL. HOURS OF WORK MAY BE RESTRICTED DURING CERTAIN HOURS OF THE DAY ON ALL ROADS AND STREETS PER WHATCOM COUNTY CODE 12.28.150 HOURS OF WORK. OFF HOURS AND OWNER HOLIDAYS (MEMORIAL DAY, INDEPENDENCE DAY, AND LABOR DAY) QUIET WORK IS ALLOWED WITH NO OFFSITE NOISE. WORK OUTSIDE WHATCOM COUNTY PUBLIC WORKS ALLOWABLE WORK HOURS SHALL BE APPROVED IN WRITING BY THE OWNER.
5. DRAWINGS INDICATE GENERAL AND TYPICAL DETAILS OF CONSTRUCTION. WHERE CONDITIONS ARE NOT SPECIFICALLY INDICATED BUT ARE OF SIMILAR CHARACTER TO DETAILS SHOWN, SIMILAR DETAILS OF CONSTRUCTION SHALL BE USED, SUBJECT TO REVIEW AND APPROVAL BY THE ENGINEER.
6. THE EXISTING TOPOGRAPHIC AND PHYSICAL FEATURES SHOWN ON THESE PLANS ARE BASED ON A FIELD SURVEY BY PACIFIC SURVEYING AND ENGINEERING, DECEMBER OF 2017, RECORD DRAWINGS, AND FIELD RECONNAISSANCE BY RH2 ENGINEERING.
7. THE CONTRACTOR SHALL PROTECT BUILDINGS, FENCES, APPURTENANCES, ABOVE GROUND UTILITIES, AND OTHER PROPERTY ADJACENT TO ALL CONSTRUCTION AREAS. THE CONTRACTOR SHALL BE SOLELY RESPONSIBLE FOR REPAIRING ALL DAMAGE CAUSED BY CONSTRUCTION ACTIVITIES.
8. THE CONTRACTOR SHALL CONTAIN WORK TO WITHIN PARCEL 'A' (D STATION).
9. ANY REVISIONS TO PLANS MUST BE REVIEWED BY THE ENGINEER AND APPROVED BY THE OWNER PRIOR TO ANY IMPLEMENTATION IN THE FIELD.
10. CONTRACTOR SHALL TAKE NECESSARY PRECAUTIONS TO LOCATE AND PROTECT ALL EXISTING SURVEY MONUMENTS DURING CONSTRUCTION. ALL SURVEY MONUMENTS THAT MAY BE DISTURBED BY CONSTRUCTION SHALL BE IDENTIFIED, REFERENCED, AND REPLACED IN ACCORDANCE WITH RECOGNIZED SURVEYING PRACTICES BY A LICENSED LAND SURVEYOR PROVIDED BY THE CONTRACTOR.

1. THE LOCATION AND ELEVATIONS OF EXISTING UTILITIES INDICATED ON THE DRAWINGS ARE APPROXIMATE AND HAVE BEEN PLOTTED FROM THE INFORMATION AVAILABLE TO THE ENGINEER. THE SOURCE OF INFORMATION GENERALLY CONSISTS OF FIELD SURVEY, AVAILABLE RECORDS SUPPLIED BY THE OWNER OR THROUGH VERBAL COMMUNICATIONS WITH THE OWNER'S STAFF. THE OWNER AND ENGINEER DO NOT GUARANTEE AND ASSUME NO RESPONSIBILITY FOR THE ACCURACY OF THIS INFORMATION. THE CONTRACTOR SHALL DETERMINE THE EXACT LOCATION OF ALL EXISTING UTILITIES PRIOR TO COMMENCING WORK TO AVOID DAMAGE OR DISTURBANCE, AND AGREES TO BE FULLY RESPONSIBLE FOR ANY AND ALL DAMAGES WHICH MIGHT BE CAUSED BY THE CONTRACTOR'S FAILURE TO ACCURATELY LOCATE AND PRESERVE ALL UNDERGROUND UTILITIES. IT IS UNDERSTOOD THAT OTHER ABOVE GROUND AND UNDERGROUND FACILITIES NOT SHOWN ON THE PLANS MAY BE ENCOUNTERED DURING THE COURSE OF WORK.

1. THE CONTRACTOR SHALL COVER ALL TRENCH CUTS AT THE END OF EACH WORKING DAY WITH STEEL SHEETS WHERE REGULAR CROSSINGS ARE MADE.

1. ALL EXISTING VALVES SHALL BE OPERATED BY THE OWNER.
2. ALL WATER PIPE AND APPURTENANCES SHALL BE LEAD FREE IN ACCORDANCE WITH THE SAFE DRINKING WATER ACT, SECTION 1417
3. ALL DISTURBED AREAS SHALL BE RESTORED TO PRE-CONSTRUCTION CONDITION.

1. CONTRACTOR SHALL PREPARE A PROJECT SPECIFIC CONSTRUCTION STORMWATER POLLUTION PREVENTION PLAN. SEE TECHNICAL SPECIFICATIONS DIVISION 2 FOR MORE INFORMATION.

- ## SECTION AND DETAIL REFERENCES



DETAIL/SECTION REFERENCE BUBBLE - REFERS READER TO THE DRAWING ON WHICH THE DETAIL OR SECTION IS LOCATED.

WHERE, X = SECTION/DETAIL REFERENCE NUMBER  
X000 = DRAWING NUMBER ON WHICH DETAIL ORIGINATED OR RESIDES

SECTION REFERENCE LETTER CONVENTIONS:  
SECTIONS OR ELEVATIONS SHOULD HAVE A LETTER REFERENCE (A THROUGH ZZ)  
DETAIL REFERENCE NUMBER CONVENTIONS:  
DETAIL REFERENCES SHOULD HAVE A NUMBER REFERENCE (100 THROUGH 900).

## ABBREVIATIONS

APPROX	APPROXIMATE	LF	LINEAR FEET
CB	CATCH BASIN	N	NORTHING
CL	CENTERLINE	OCM	OVERHEAD COMMUNICATIONS
CMP	CORRUGATED METAL PIPE	OHE	OVERHEAD ELECTRICAL
CO	COUNTY	OHP	OVERHEAD POWER
CONC	CONCRETE	PE	POLYETHYLENE
CSBC	CRUSHED SURFACING BASE COURSE	PROP	PROPOSED
CSCT	CRUSHED SURFACING TOP COURSE	PUD	PUBLIC UTILITY DISTRICT (OWNER)
DI	DUCTILE IRON	PVC	POLYVINYL CHLORIDE
DIA	DIAMETER	RD	ROAD
DWG	DRAWING	REQ'D	REQUIRED
E	EASTING	ROW	RIGHT OF WAY
ELEV	ELEVATION	SPEC	SPECIFICATIONS
EX	EXISTING	SS	SANITARY SEWER
FL	FLANGED	SSMH	SANITARY SEWER MANHOLE
G	GAS	ST	STORM
HMA	HOT MIXED ASPHALT	SY	SQUARE YARDS
HDG	HOT DIPPED GALVANIZED	TYP	TYPICAL
IE	INVERT ELEVATION	UNK	UNKNOWN
		W	WATER

## SURVEY NOTES

- VISIBLE & SURFACE UTILITIES ARE SHOWN AS MAPPED BY PACIFIC SURVEYING AND ENGINEERING INC. (PSE). DETECTIBLE BURIED UTILITIES PAINTED BY A.P.S. IN DECEMBER 2017.
- DATA FOR THIS SURVEY WAS GATHERED BY FIELD TRAVERSE UTILIZING ELECTRONIC DATA COLLECTION IN DECEMBER 2017.
- EQUIPMENT USED: THEOMAT 0001.5"
  - EDM: ± 2 PPM, ± 3 MM
- VERTICAL DATUM: NGVD29
- SURVEY CONTROL POINT #11571 (SHOWN HERON) EL=121.90'
- HORIZONTAL DATUM: WA. STATE PLANE NORTH ZONE NAD 83/91
- BASIS OF BEARINGS: FOUND SECTION MONUMENTS ON THE SOUTH LINE OF SECTION 8, BEARING N88°24'32"W AS SHOWN
- CONTOUR INTERVALS ARE 1 FOOT AND ARE COMPUTER GENERATED FROM GROUND FIELD TOPOGRAPHY GATHERED FOR THIS SURVEY UTILIZING ELECTRONIC DATA COLLECTION AS SHOWN HERON.
- THIS TOPOGRAPHY MAP WAS COMPLETED WITHOUT THE BENEFIT OF A TITLE RECORD. PARCEL LINES, EASEMENT LINES, & RIGHT OF WAY MARGINS ARE SHOWN PER AVAILABLE RECORD INFORMATION. A BOUNDARY SURVEY WAS NOT PERFORMED AND NO BOUNDARY MONUMENTS WERE SET DURING THIS SURVEY.

## PIPE LENGTH MEASUREMENTS

PIPE LENGTHS CALLED OUT ON PLANS ARE MEASURED AS FOLLOWS:


FLANGE x FLANGE (FLxFL) PIPE  
MEASURED FROM FACE OF  
FLANGE TO FACE OF FLANGE.

FLANGE x PLAIN END (FLxPE) PIPE  
MEASURED FROM FACE OF  
FLANGE TO CENTER OF FITTING.

PLAIN END x PLAIN END (PExPE) PIPE  
MEASURED FROM CENTER OF  
FITTING TO CENTER OF FITTING.

RESTRAINED JOINT x  
RESTRAINED JOINT (RJxRJ) PIPE  
MEASURED FROM CENTER OF  
FITTING TO CENTER OF FITTING.

NOTE: FITTINGS ARE ASSUMED TO BE STANDARD LENGTH 125#, 250# FLANGED OR COMPACT CLASS 350 MECHANICAL JOINTS. CONTRACTOR RESPONSIBLE FOR VERIFYING LENGTHS. IT IS THE CONTRACTOR'S RESPONSIBILITY TO TAKE INTO ACCOUNT ANY VARIATIONS IN FITTING DIMENSIONS.



SIGNED: 04/13/2023





SIGNED: 04/13/2023

**PUBLIC UTILITY DISTRICT NO. 1 OF WHATCOM COUNTY  
D STATION - FLOW AND CONTROL  
IMPROVEMENTS**

## LEGEND AND GENERAL NOTES

[illegible]



## GENERAL NOTES

- CONNECTIONS TO THE NEW MAIN WILL REQUIRE SHUT DOWN OF THE MAIN WATER FEED TO BP WHICH IS USED FOR FIRE SUPPRESSION. THE CONTRACTOR SHALL PROVIDE A SCHEDULE AT THE PRECONSTRUCTION MEETING OF WHEN THE SHUTDOWN WILL OCCUR. THE CONTRACTOR SHALL AGAIN NOTIFY THE OWNER AND BP A MINIMUM OF 14 CALENDAR DAYS IN ADVANCE OF THE SHUTDOWN. SHUT DOWNS WILL BE LIMITED TO A MAXIMUM OF 4 HOURS AND CANNOT BE WITHIN 48 HOURS OF EACH OTHER.
- CONSTRUCTION SHALL BE LIMITED TO THE D STATION PROJECT SITE WITHIN THE CHAINLINK FENCE. THIS AREA IS DEFINED AS THE CONSTRUCTION LIMITS.
- ALL MATERIALS SHALL BE PROPERLY DISPOSED OF AT A CONTRACTOR-PROVIDED DISPOSAL SITE PER WSDOT SPECIFICATION SECTION 2-03.3/7C.

## DEMOLITION NOTES


FOR PHASING PLAN AND NOTES, REFER TO DWG. NO. C02.



- REMOVE EXISTING ELECTRICAL EQUIPMENT AND RETURN TO OWNER.
- PLUG ANY PENETRATIONS INTO THE PIPE WITH APPROPRIATELY SIZED FITTINGS TO ENSURE NO LEAKAGE.
- REMOVE EXISTING SUMP PUMP AND PIPING AND RETURN TO OWNER
- REMOVE EXISTING ELECTRICAL EQUIPMENT AND RETURN TO OWNER.
- ABANDON STEPS IN MANHOLE




REMOVE RING AND COVER AND RETURN TO OWNER	SURGE TANK (PROTECT IN PLACE)
	D STATION ABOVE GRADE STRUCTURE (PROTECT IN PLACE)
REMOVE STRUCTURE BELOW GRADE AS NOTED ON THIS SHEET.	D STATION BELOW GRADE STRUCTURE (PROTECT IN PLACE)
REMOVE SUMP PUMP PIPING.	




APPROX. LOCATION  
OF NEW WATER MAIN  
PIPING

EXISTING METER  
ACCESS STRUCTURE  
TO BE ABANDONED


SUMP PUMP  
DISCHARGE PIPING  
TO BE REMOVED






PHASE 1 PLAN

1" = 10'




PHASE 3 PLAN

1" = 10'



PHASE 2 PLAN

1" = 10'



PHASE 4 PLAN

1" = 10'



## PHASING LEGEND

	EXISTING PIPING
	EXISTING PIPING TO BE REMOVED
	CURRENT PHASE PIPING
	PREVIOUS PHASE PIPING

## PHASING NOTES

PHASING PLAN SHOWN IN SCHEMATIC AND THE CONTRACTOR SHALL SUBMIT A PHASING PLAN TO THE DISTRICT FOR REVIEW AND APPROVAL PRIOR TO ANY EXCAVATION WORK. SUGGESTED PHASING IS AS FOLLOWS:

- SHUT OFF MAIN VALVE AND REMOVE BLIND FLANGES ON CENTER AND SOUTH PIPES TO INSTALL NEW VALVES. BLIND FLANGE SOUTH VALVE.
- WORK ON EXTERIOR TO 90° BEND. BLIND FLANGE AND PRESSURE TEST PIPE PER SPECIFICATIONS SECTION 15.18.02.
- INSTALL TEE AT NORTH END OF OLD LINE AND TIE IN 90° BEND ON SOUTH END OF OLD LINE. PRESSURE TEST AND BRING ONLINE.
- INSTALL REMAINING PIPE, VAULT, METER, VALVES, AND TEES. PRESSURE TEST AND BRING ONLINE.
- EXISTING CONTROL VALVE SHALL BE LEFT IN PLACE AND USED TO FACILITATE SHUT DOWNS.

NOTE: PROPOSED PIPE, FITTINGS, AND APPURTENANCES ARE DETAILED ON DWG NO. C03.



SIGNED: 04/13/2023



SIGNED: 04/13/2023

PUBLIC UTILITY DISTRICT NO. 1 OF WHATCOM COUNTY  
D STATION - FLOW AND CONTROL  
IMPROVEMENTS

PUBLIC UTILITY  
DISTRICT No. 1  
of Whatcom County


## PHASING PLAN

NO.	DATE	DESCRIPTION	BY	REVIEW

### REVISIONS

ENGINEER: OMP  
REVIEWED: DWB  
DATE: Apr 13, 2023  
FILENAME: DSTA-D-PHASING.DWG  
JOB NO.: 21-0163

SCALE: SHOWN
0" 1" 2"
DRAWING IS FULL SCALE WHEN BAR MEASURES 2"
DWG NO.: C02
SHEET NO.: 4
20



- GENERAL NOTES
- 1) GRAVEL RESTORATION ELEVATIONS SHALL MATCH EXISTING. GRADE GRAVEL IN A MANNER TO PREVENT ANY LOW POINTS IN THE RESTORED LOCATIONS. SURFACE RESTORATION SHALL BE 4" GRAVEL TOP COURSE PER SPECIFICATIONS SECTION 2.11.8.

2) PROVIDE ANODES WHERE INDICATED ( ). SEE DETAILS ON DWG NO. C05 FOR ADDITIONAL INFORMATION.

3) PIPE TRENCH SHALL BE PER DETAIL ON DWG NO. C05.

4) ALL COUPLINGS ARE TO BE FULLY RESTRAINED THROUGH THE USE OF ANCHOR PINS OR AN APPROVED EQUIVALENT.

5) PROVIDE POLYETHYLENE ENCASUREMENT PER DETAIL ON DWG NO. C04 FOR ALL BURIED PIPING.

6) ALL BURIED VALVES SHALL HAVE VALVE BOXES PER DIVISION 15.40.08. VALVE BOX ASSEMBLY SHALL BE ADJUSTABLE TO ACCOMMODATE TRENCH DEPTH.

7) CONCRETE HORIZONTAL THRUST BLOCKING SHALL BE PER DETAIL ON DWG NO. C05.

8) CONCRETE REVERSE THRUST BLOCKING SHALL BE PER DETAIL ON DWG NO. C05. SHACKLE RODS SHALL BE ATTACHED TO FITTINGS ON EITHER SIDE OF REVERSE BLOCKS, TYP.

RH2

DANIEL L. BURBULE

35309

REGISTERED PROFESSIONAL ENGINEER

SIGNED: 04/13/2023

ARIN M. PAUL

57679

REGISTERED PROFESSIONAL ENGINEER

SIGNED: 04/13/2023

PUBLIC UTILITY DISTRICT NO. 1 OF WHATCOM COUNTY

D STATION - FLOW AND CONTROL IMPROVEMENTS

PUBLIC UTILITY DISTRICT No. 1 of Whatcom County

PROPOSED SITE PLAN

ENGINEER: OMP  
REVIEWED: DWB

DATE: Apr 13, 2023  
PLOT DATE: Apr 13, 2023

CLIENT: WPUD  
FILE NAME: DSTA-D-CIV.DWG

LOG NO.: 21-0163

REVISIONS

NO.	DATE	DESCRIPTION	BY	REVIEW


SCALE: SHOWN

0" 1" 2"

DRAWING IS FULL SCALE WHEN BAR MEASURES 2"

DWG NO.: C03  
SHEET NO.: 5

20



INSTALLATION PROCEDURES FOR POLYETHYLENE ENCASEMENT ON BELL AND SPIGOT PIPE:

- CUT THE POLYETHYLENE TUBE TWO FEET LONGER THAN PIPE AND SLIP OVER CLEAN PIPE STARTING AT THE SPIGOT END. CIRCUMFERNETIALLY TAPE THE SPIGOT END OF THE TUBE TO THE PIPE BARREL BEHIND THE INSERTION LINE SO IT WILL BE AS CLOSE AS POSSIBLE TO THE FACE OF THE BELL AFTER ASSEMBLY WITHOUT INTERFERING WITH THE GASKET.
- TAKE UP SLACK IN THE TUBE ALONG THE PIPE BARREL WITH PVC TAPE, MAKING A SNUG BUT NOT TIGHT FIT. FOLD OVER ON TOP OF PIPE AND SECURE IN PLACE WITH 2 LAYERS OF CIRCUMFERENTIALLY WRAPPED TAPE.
- SPREAD THE POLYETHYLENE TUBE AS SHOWN AND APPLY CIRCUMFERENTIAL WRAPS OF TAPE EVERY TWO FEET ON CENTER UNTIL YOU RUN OUT OF ROOM.
- DIG A SHALLOW BELL HOLE IN THE TRENCH BOTTOM, LOWER THE PIPE (ENSURING OVERLAP IS ORIENTED AS SHOWN), AND MAKE UP THE JOINT. SLIDE THE SLING TO THE BELL END AND LIFT PIPE TO PROVIDE CLEARANCE TO SLIDE ENCASEMENT TO THE END, ENSURING NO DEBRIS IS ON PIPE OR ENTERS ENCASEMENT. CONTINUE FOLDING SNUGLY AND TAPING.
- PULL POLYETHYLENE FORWARD FROM PREVIOUS JOINT OVER THE BELL, ENSURING THERE ARE AT LEAST 12" OF OVERLAP. SECURE WITH TAPE AT THE OVERLAP AND BEHIND THE PRECEDING BELL.

GENERAL NOTES:

- REPAIR MINOR DAMAGE TO POLYETHYLENE ENCASEMENT WITH ADHESIVE TAPE OR WITH AN ADDITIONAL SHEET OF POLYETHYLENE WITH EDGES SEALED WITH ADHESIVE TAPE.
- IN AREAS WITH NO GROUNDWATER AND NO PRECIPITATION IN FORECAST DURING INSTALLATION, A PIECE OF TAPE EVERY 6 FEET (OR MORE OFTEN AS REQUIRED) MAY BE USED IN LIEU OF FULL CIRCUMFERENTIAL WRAPPING EVERY 2 FEET. FULL CIRCUMFERENTIAL TAPE AT SPIGOT END AND ON EITHER SIDE OF BELL IS STILL REQUIRED.
- FOR ODD-SHAPED APPURTENANCES, WRAP WITH A FLAT SHEET OR SPLIT LENGTH OF TUBE BY PASSING THE SHEET UNDER THE APPURTENANCE AND BRINGING THE SHEET AROUND THE BODY. MAKE SEAMS BY BRINGING THE EDGES OF THE POLYETHYLENE SHEET TOGETHER, FOLDING THEM OVER TWICE, AND TAPING THEM. TAPE THE POLYETHYLENE SECURELY IN PLACE AT THE VALVE STEM AND OTHER PENETRATIONS.
- WHERE POLYETHYLENE-WRAPPED PIPE JOINS AN ADJACENT PIPE THAT IS NOT WRAPPED, EXTEND THE POLYETHYLENE WRAP TO COVER THE ADJACENT PIPE FOR A DISTANCE OF AT LEAST 3 FT. SECURE THE END WITH CIRCUMFERENTIAL WRAPS OF ADHESIVE TAPE.
- SERVICE LINES OF DISSIMILAR METALS SHALL BE WRAPPED WITH POLYETHYLENE OR DIELECTRIC TAP FOR A MINIMUM CLEAR DISTANCE OF 3' AWAY FROM THE DUCTILE IRON PIPE.

POLYETHYLENE ENCASEMENT DETAIL


NOT TO SCALE

ITEM	WIRE COLOR	WIRE
NEW WATER MAIN	WHITE	8 AWG STRANDED COPPER WIRE, USE-TYPE INSULATION
EXISTING WATER MAIN	BLACK	8 AWG STRANDED COPPER WIRE, USE-TYPE INSULATION
ZINC REFERENCE CELL	YELLOW	12 AWG SOLID COPPER WIRE, TW OR THHN INSULATION
CP MONITORING COUPONS	PURPLE	12 AWG STRANDED COPPER WIRE, TW OR THHN INSULATION

NOTES:

- WIRE SHALL HAVE ENOUGH SLACK TO EXTEND A MIN OF 2 FT ABOVE FINISHED GRADE AFTER FINAL PAVING.
- FOR AN ISOLATION JOINT RUN OF NEW WATER PIPE, WIRE ON THE UP STATION SIDE OF THE ISOLATION JOINT SHALL BE WHITE AND WIRE ON THE DOWN STATION SIDE OF THE ISOLATION JOINT SHALL BE BLACK.
- COLOR CODE WIRES BY INSULATION COLOR, OR BY COLORED TAPE OR PAINT ON LAST 4 FT OF WIRE.


CORROSION CONTROL TEST WIRE IDENTIFICATION TABLE



POLYETHYLENE ENCASEMENT AT MECHANICAL JOINTS NOTE:  
WHERE THE POLYETHYLENE ENCASEMENT CAN BE PUNCTURED OR TORN BY FITTINGS OR BOLTS, INSTALL 40 MIL GEOMEMBRANE AROUND FITTING/JOINT. TAPE THE ENDS AND SEAMS OF THE GEOMEMBRANE WITH PVC TAPE AND THEN COVER THE PIPE JOINT WITH THE ADJOINING POLYETHYLENE ENCASEMENT.

POLYETHYLENE ENCASEMENT AT MECHANICAL JOINTS/SIMILAR

NOT TO SCALE




100  
M01

PIPE PENETRATION DETAIL

NOT TO SCALE

PIPE SUPPORT NOTES:

- CONTRACTOR SHALL PROVIDE SUPPORTS AS NEEDED TO SECURE PIPING SYSTEM IN NORMAL AND TESTING CONDITIONS. CONTRACTOR IS RESPONSIBLE FOR DESIGN OF THE NECESSARY PIPE SUPPORTS, HANGERS AND SEISMIC BRACING. SEE SPECIFICATIONS FOR ADDITIONAL INFORMATION.
- SADDLE AND SADDLE CLAMP SUPPORTS SHALL BE "STANDON" BRAND AS MANUFACTURED BY MATERIAL RESOURCES OR EQUAL.




TYPE C - SADDLE CLAMP SUPPORT

(TYP. AT PIPING)

101  
M01

PIPE SUPPORT DETAIL


NOT TO SCALE



FLANGE JOINT NOTE:  
HIGH STRENGTH BOLTS REQUIRE (2) ADDITIONAL HIGH STRENGTH, STEEL WASHERS.


DIELECTRIC ISOLATION: FLANGE JOINT DETAIL

NOT TO SCALE



TEST STATION INSTALLATION

NOT TO SCALE




NOTE:  
ISOLATION FLANGE JOINT SHOWN, OTHERS SIMILAR.


ISOLATION JOINT MONITORING TEST STATION (TS/IJ/M)

NOT TO SCALE

RH2



SIGNED: 04/13/2023



SIGNED: 04/13/2023



PUBLIC UTILITY DISTRICT NO. 1 OF WHATCOM COUNTY  
D STATION - FLOW AND CONTROL  
IMPROVEMENTS

PUBLIC UTILITY  
DISTRICT No. 1  
of Whatcom County

SITE DETAILS I

LOG NO.	CLIENT	FILENAME	ENGINEER	DATE	REVISIONS	DATE	DESCRIPTION	NO.	DATE	REVIEW
21-0163	WPUD	DSTA-D-CV.DWG	APR 13, 2023	APR 13, 2023						



SCALE: SHOWN	1" = 2'
DWG NO.: C04	SHEET NO.: 6
	20



102 C05 **EXOTHERMIC WELD DI & STEEL PIPE**

NOT TO SCALE


THRUST BLOCK SIZING TABLE						
Diameter Size (inches)	Fitting	Thrust force (lb)	Bearing block area (sf)	Depth, D (ft)	Width, W (ft)	Thickness, T (ft)
18	TEES/DEAD ENDS	67,196	67.2	5.8	11.6	10.1
NOTES	TEST PRESSURE: 225 POUNDS PER SQUARE INCH (PSI)					
	SOIL BEARING CAPACITY: 1,500 POUND PER SQUARE FOOT (PSF), GLACIAL DRIFT MATERIAL FACTOR OF SAFETY: 1.5					




**REVERSE THRUST BLOCK DETAIL**

NOT TO SCALE

SIZING TABLE					
PIPE DIA.	Bearing Area (Min.)	H (Min.)	L (Min.)	T (Min.)	REINFORCING
18"	57.3 SF	6.1'	11.9'	2.5'	#4 @ 6" OC EW



- NOTES**
- MAINTAIN 18" MINIMUM COVER OVER THE TOP OF BLOCK.
  - BOTTOM OF BLOCK IS TO BE ON UNDISTURBED SOIL.
  - TRENCH TO BE BACKFILLED AND COMPACTED TO 95% DENSITY ON ALL SIDES OF BLOCK AND A DISTANCE OF 4' MIN. IN FRONT OF BLOCK TO FULL DEPTH OF BLOCK.
  - IF BLOCK CANNOT BE KEYED INTO UNDISTURBED SOIL TO THE SATISFACTION OF THE DISTRICT, A) THE BLOCK LENGTH SHALL BE EXTENDED TO PROVIDE AN ADEQUATE KEY OR B) CDF SHALL BE USED TO FILL BACK TO NATIVE SOIL OR C) THE TRENCH SHALL BE BACKFILLED AND COMPACTED TO 95% DENSITY A MINIMUM DISTANCE OF 15 FEET IN FRONT OF THE BLOCK TO THE SATISFACTION OF THE DISTRICT.
  - DESIGN CONSIDERATIONS:  
TEST PRESSURE: 225 PSI  
SOIL BEARING CAPACITY: 1,500 PSF  
FACTOR OF SAFETY: 1.5



THRUST BLOCK - TEE/DEAD ENDS


**HORIZONTAL THRUST BLOCKING**

NOT TO SCALE

- NOTES:**
- ALL DIMENSIONS APPLY TO STABLE TRENCH WALLS. UNDER VARIABLE CONDITIONS, SIZE OF THRUST BLOCK SHALL BE DETERMINED BY THE ENGINEER.
  - WRAP ALL FITTINGS WITH VISQUEEN MIN. 6" PAST FLANGES, PRIOR TO POURING CONCRETE THRUST BLOCK.



SIGNED: 04/13/2023




SIGNED: 04/13/2023

PUBLIC UTILITY DISTRICT NO. 1 OF WHATCOM COUNTY  
**D STATION - FLOW AND CONTROL IMPROVEMENTS**

**SITE DETAILS II**




ENGINEER: OMP	SAFE DATE: Apr 13, 2023	CLIENT: WPUD	LOG NO.: 21-0163	REVISIONS	NO.	DATE	DESCRIPTION	BY	REVIEW
REVIEWED: DWB	PLOT DATE: Apr 13, 2023	FILENAME: DSTA-D-CIV.DWG							

SCALE: SHOWN	
0'	1' 2'
DRAWING IS FULL SCALE WHEN BAR MEASURES 2"	
DWG NO.: C05	SHEET NO.: 7



- NOTES:
- SEE DIVISION 8 OF THE SPECIFICATIONS FOR HARDWARE GROUP SCHEDULE.
  - BUILDING COATINGS PER DIVISION 9 OF THE SPECIFICATIONS.

DOOR AND FRAME SCHEDULE								
		DOOR			FRAME			NOTES
DOOR NO.	TYPE	SIZE		MATERIAL	SIZE		MATERIAL	
		WIDTH	HEIGHT		WIDTH	HEIGHT		
0101	1	3'-0"	6'-8"	STEEL	3'-4"	6'-10"	STEEL	
								PROVIDE DOOR HARDWARE TO DOORS AS SPECIFIED IN DIVISION 8. PANIC BARS SHALL BE PROVIDED FOR EXTERIOR DOOR.





SIGNED: 04/13/2023



SIGNED: 04/13/2023

PUBLIC UTILITY DISTRICT NO. 1 OF WHATCOM COUNTY

**D STATION - FLOW AND CONTROL IMPROVEMENTS**

PUBLIC UTILITY DISTRICT No. 1 of Whatcom County

**BUILDING ELEVATIONS**

ENGINEER: OMP	DATE: Apr 13, 2023	CLIENT: WPUD	LOGO NO.: 21-0163	REVISIONS	NO.	DATE	DESCRIPTION	BY	REVIEW
REVIEWED: DWB	PLOT DATE: Apr 13, 2023	FILENAME: DSTA-D-STRP.DWG							

SCALE: SHOWN

0" 1" 2"

DRAWING IS FULL SCALE WHEN BAR MEASURES 2"

DWG NO.: S01 SHEET NO.: 8 20

GENERAL STRUCTURAL NOTES



GENERAL:

- G1. SCOPE  
THE NOTES ON THIS SHEET AND THE STANDARD STRUCTURAL DETAILS ARE GENERAL AND APPLY TO THE ENTIRE PROJECT WHETHER SPECIFICALLY CALLED OUT OR NOT, EXCEPT WHERE THERE ARE SPECIFIC INDICATIONS TO THE CONTRARY ON STRUCTURAL SHEETS. IF THERE ARE QUESTIONS, THEY SHALL BE SUBMITTED TO THE STRUCTURAL ENGINEER AND ANSWERED IN WRITING PRIOR TO CONSTRUCTION.
- G2. APPLICABLE SPECIFICATIONS AND CODES  
ALL MATERIALS, WORKMANSHIP, DESIGN, AND CONSTRUCTION SHALL CONFORM TO THE DRAWINGS, SPECIFICATIONS, AND THE INTERNATIONAL BUILDING CODE (2018 EDITION).  
A. INTERNATIONAL BUILDING CODE: IBC 2018 WITH APPLICABLE EDITIONS OF THE CODE REFERENCED STANDARDS.  
B. AMERICAN CONCRETE INSTITUTE: ACI 350-(01), (06)  
C. LOCAL JURISDICTION AMENDMENTS: WHATCOM COUNTY
- G3: DESIGN CRITERIA  
A. BASIC WIND SPEED: 105 MPH  
B. ROOF SNOW LOAD: 25 PSF  
C. ROOF LIVE LOAD: 20 PSF  
D. SEISMIC, Sds: 0.91 g  
E. FLOOR LIVE LOAD: 125 PSF
- G4. SAFETY  
SAFETY AND STRUCTURAL STABILITY DURING CONSTRUCTION ARE THE SOLE RESPONSIBILITY OF THE CONTRACTOR. STRUCTURES HAVE BEEN DESIGNED TO RESIST THE DESIGN LOADS ONLY AS A COMPLETED STRUCTURE.
- G5. GENERAL  
LINES SHOWN ON DRAWINGS MAY BE ASSOCIATED WITH CAD MODELING AND MAY NOT REPRESENT REQUIRED OR ALLOWED JOINTS. SEE DETAILS FOR CLARIFICATION ON REQUIRED AND ALLOWED JOINTS.
- G6. OPENINGS  
OPENINGS FOR PIPES, DUCTS, CONDUITS, ETC. ARE NOT ALL SHOWN ON THE STRUCTURAL DRAWINGS. COORDINATE AND PROVIDE OPENINGS AS REQUIRED TO ACCOMMODATE ALL WORK SHOWN OR SPECIFIED IN TECH CONTRACT DOCUMENTS AND OTHERWISE REQUIRED FOR FURNISHING OF A FUNCTIONALLY COMPLETE PROJECT. REINFORCE AROUND OPENINGS PER STANDARD STRUCTURAL DETAILS UNLESS OTHERWISE SHOWN.
- G7. SPECIAL INSPECTIONS  
SPECIAL INSPECTIONS ARE REQUIRED IN ACCORDANCE WITH CHAPTER 1 AND CHAPTER 17 OF THE IBC (CBC). PAYMENT FOR THESE INSPECTIONS IS NOT THE RESPONSIBILITY OF THE CONTRACTOR. THE CONTRACTOR SHALL PROVIDE FOR FULL ACCESS TO THE WORK BY THE SPECIAL INSPECTOR AND SHALL PROVIDE FOR THESE INSPECTIONS IN THEIR CONSTRUCTION SCHEDULE IN ACCORDANCE WITH THE SPECIFICATIONS.
- G8. STANDARD DETAILS  
THE STANDARD DETAILS DEPICT TYPICAL DETAILING TO BE USED ON THIS PROJECT. IF CONDITIONS ARE NOT EXPLICITLY SHOWN ON THE DRAWING THEY SHALL BE MADE SIMILAR TO THE STANDARD DETAILS. OBTAIN APPROVAL OF ENGINEER IN WRITING FOR SIMILAR CONDITIONS PRIOR TO CONSTRUCTION.
- G9. THE CONTRACTOR SHALL FIELD VERIFY ALL DIMENSIONS AND ELEVATIONS OF EXISTING CONSTRUCTION AS REQUIRED TO COORDINATE NEW CONSTRUCTION. SUBMIT REQUIRED CHANGES FOR APPROVAL.
- G10. CONTRACTOR TO SUBMIT FOR REVIEW ALL EQUIPMENT SIZES, OPERATING WEIGHTS, VIBRATION FORCES, SUPPORT LOCATIONS, ALONG WITH ANY FLOOR OPENINGS, NOTCHES, AND RECESS REQUIRED BY SUCH EQUIPMENT. CONCRETE SUPPORT PADS AND/OR FRAMING REQUIRED TO SUPPORT SAID EQUIPMENT SHALL NOT BE FABRICATED.

STEEL

- S1. DESIGN STRENGTHS:  
WIDE FLANGE AND TEES: FY = 50 KSI  
PIPES: FY = 35 KSI  
STAINLESS STEEL: FY = 33 KSI  
HSS SECTIONS: FY = 46 KSI  
ALL OTHER PLATES AND SHAPES: FY = 36 KSI
- S2. DIMENSIONS  
TO CENTERLINES OF COLUMNS AND BEAMS, TOP SURFACES OF BEAMS AND TUBES AND BACKS OF CHANNELS AND ANGLES, UNO.
- S3. ELEVATIONS  
TOP OF STEEL REFERS TO TOP OF SURFACE OF MEMBER OR FLANGE UNO.
- S4. WHEN FILLET WELD SIZE IS NOT INDICATED, PROVIDE MAXIMUM WELD SIZE BASED ON MATERIAL THICKNESS IN ACCORDANCE WITH AISC SPECIFICATIONS.
- S5. ALL BOLTED STRUCTURAL CONNECTIONS ARE BEARING TYPE CONNECTIONS UNLESS OTHERWISE SPECIFIED TO BE SLIP-CRITICAL. PROVIDE LOAD INDICATING WASHERS AT SLIP-CRITICAL CONNECTIONS.
- S6. CONFORM TO AISC 360, STEEL CONSTRUCTION MANUAL AND AISC 341, SEISMIC DESIGN MANUAL.
- S7. THE SEISMIC LOAD RESISTING SYSTEM (SLRS) IS DENOTED ON THE FRAMING PLANS AND FRAME ELEVATIONS. THE SLRS DESIGNATION INCLUDES THE MEMBER AND CONNECTION AT EACH END. FRAMES ARE DENOTED AS FOLLOWS:  
A. MOMENT FRAME: (SLRS)

B. CONCENTRICALLY BRACED FRAME: (SLRS)

FOR SLRS SYSTEMS OR PARTS OF SYSTEMS THAT ARE NOT INCLUDED IN FRAMES, (SLRS) IS PLACED NEXT TO THE BEAM SIZE ON THE FRAMING PLAN (EG: ON A COLLECTOR ELEMENT(DRAG STRUT): MEMBER DESIGNATION (SLRS)

S8. ALL STEEL BEAMS SHALL RECEIVE STANDARD CAMBER PER THE SPECIFICATIONS UNLESS NOTES OTHERWISE ON THE PLANS. BEAMS REQUIRING SPECIAL CAMBER ARE DENOTED ON THE BEAMS SHOWN ON THE FRAMING PLANS: EXAMPLE (+1/2") INDICATES 1/2".

CONCRETE

- C1. DESIGN STRENGTHS:  
FC = 4,000 PSI  
FY = 60,000 PSI
- C2. CONCRETE COVER  
UNLESS OTHERWISE NOTES, PROVIDE CONCRETE COVER FOR REINFORCED CONCRETE DEPOSITED AGAINST EARTH: 3"  
TIE REINFORCING AT COLS AND PILASTERS: 1 1/2"  
ALL OTHERS: 2"  
SEE DRAWINGS FOR EXCEPTIONS
- C3. SEE SPECIFICATIONS FOR REINFORCING PLACEMENT REQUIREMENTS
- C4. REFER TO OTHER DISCIPLINE DRAWINGS PRIOR TO CONSTRUCTION FOR EMBEDDED ITEMS AND PENETRATIONS NOT SHOWN ON STRUCTURAL DRAWINGS. AS REQUIRED TO ACCOMMODATE ALL WORK SHOWN OR SPECIFIED IN THE CONTRACT DOCUMENTS AND OTHERWISE REQUIRED FOR THE FURNISHING OF A FUNCTIONALLY COMPLETE PROJECT REINFORCE AROUND OPENINGS PER STANDARD STRUCTURAL DETAILS UNLESS OTHERWISE SHOWN.
- C5. PROVIDE 3/4" CHAMFERS AT ALL EXPOSED EDGES (AND 1/2" CHAMFERS AT JOINTS AS SHOWN) NOT ALL CHAMFERS MAY BE SHOWN ON DRAWINGS.
- C6. FIELD ADJUST REINFORCING AT OPENINGS AND EMBEDDED ITEMS AS INDICATED.
- C7. ANCHOR BOLTS NOT SPECIFIED BY ENGINEER SHALL BE DESIGNED AND CERTIFIED BY A REGISTERED PROFESSIONAL ENGINEER RETAINED BY THE CONTRACTOR, IN ACCORDANCE WITH APPLICABLE PROJECT AND CODE REQUIREMENTS. SUBMIT AS A SHOP DRAWING FOR REVIEW AND APPROVAL BY THE ENGINEER. COORDINATE LOCATION, SIZE AND EMBEDMENT PRIOR TO CASTING CONCRETE.
- C8. CONTINUOUS WATERSTOP SHALL BE INSTALLED IN JOINTS SUBJECT TO STATIC WATER PRESSURE.
- C9. ABSOLUTELY NO WELDING OF REINFORCING BARS OR TORCHING TO BEND REINFORCING BARS SHALL BE ALLOWED WITHOUT SPECIFIC APPROVAL FROM THE STRUCTURAL ENGINEER.
- C10. CONTRACTOR SHALL SUBMIT CONCRETE PLACEMENT PLAN (PER SPECIFICATION 03311) IDENTIFYING JOINT TYPES, JOINT LOCATIONS AND CONCRETE PLACEMENT SEQUENCE.
- C11. ALL CAST IN PLACE AND POST-INSTALLED ANCHOR INDICATED IN THE STRUCTURAL DOCUMENTS SHALL COMPLY WITH APPENDIX D OF ACI 318 AND CHAPTER 19 OF ALL THE IBC. ALL EXPANSION AND ADHESIVE ANCHORS SHALL HAVE THE ICC REPORT SHOWING EQUIVALENT LOAD CAPACITY. SUBMIT AND INSTALL PER THE ICC EVALUATION REPORT.

REINFORCED CONCRETE:

1. REINFORCING STEEL SHALL BE DETAILED (INCLUDING HOOKS AND BENDS) IN ACCORDANCE WITH ACI 315-99 AND 318-14. LAP ALL REINFORCEMENTS IN ACCORDANCE WITH THE "REINFORCING SPLICE AND DEVELOPMENT LENGTH SCHEDULE" - SEE THIS SHEET. PROVIDE CORNER BARS AT ALL WALL INTERSECTIONS PER DETAIL 303. LAP ADJACENT MATS OF WELDED WIRE FABRIC A MINIMUM OF 8" AT SIDES AND ENDS.
2. NO BARS PARTIALLY EMBEDDED IN HARDENED CONCRETE SHALL BE FIELD BENT UNLESS SPECIFICALLY DETAILED OR APPROVED BY THE STRUCTURAL ENGINEER.
3. A 6" WATERSTOP SHALL BE PLACED AT ALL BELOW GRADE CONCRETE SLAB AND WALL CONSTRUCTION JOINTS AND AS SHOWN TO PROVIDE A WATERTIGHT STRUCTURE.
4. CONCRETE PROTECTION FOR REINFORCING STEEL SHALL BE AS FOLLOWS, UNLESS OTHERWISE NOTED:  
4.1. FOOTINGS AND OTHER UNIFORMED SURFACES CAST AGAINST AND PERMANENTLY EXPOSED TO EARTH ..... 3"  
4.2. FORMED SURFACES EXPOSED TO EARTH (WALLS BELOW GRADE), WATER OR WEATHER (#6 BARS OR LARGER) ..... 2"  
4.3. COLUMN TIES OR SPIRALS AND BEAM STIRRUPS ..... 2"  
4.4. SLABS AND INTERIOR FACES ..... 2"

ABBREVIATIONS:

- AL - ALUMINUM  
CHK - CHECKERED  
CL - CENTERLINE  
CLR - CLEAR  
EA - EACH  
EF - EACH FACE  
FB - FLAT BAR  
GALV - GALVANIZED  
HORZ - HORIZONTAL  
LLV - LONG LEG VERT  
O.C. - ON CENTER  
PL - PLATE  
RB - ROUND BAR  
RST - REINF. STEEL  
SST - STAINLESS STEEL  
T&B - TOP & BOTTOM  
VERT - VERTICAL  
PJF - PREMOLDED JOINT FILLER

REINFORCEMENT SPLICE AND DEVELOPMENT SCHEDULE						
BAR	Ld, MINIMUM STRAIGHT DEVELOPMENT LENGTHS			MINIMUM LAP SPLICE LENGTHS		
	MINIMUM	TOP BARS	OTHERWISE	CLASS A	CLASS B	
#3	19"	25"	29"	Ld	1.3xLd	
#4	24"	32"	36"	Ld	1.3xLd	
#5	29"	38"	43"	Ld	1.3xLd	
#6	42"	55"	63"	Ld	1.3xLd	
"MINIMUM" IF: MIN COVER OF ONE BAR Ø AND MIN SPACING OF TWO BAR DIAMETERS MIN COVER ONE Ø, MIN SPACING OF ONE BAR Ø, AND TIES OR STIRRUPS LESS THAN 12" OF FRESH CONCRETE BELOW HORIZONTAL BARS "TOP BARS" IF: MEETS CRITERIA FOR MIN EXCEPT 12" OR MORE FRESH CONC BELOW "OTHERWISE" IF: DOES NOT MEET REQUIREMENTS FOR MIN DEVELOPMENT LENGTH "CLASS A" IF: ONLY HALF OF BARS LAPPED AT ONE LOCATION AND TWICE THE REINFORCING FOR TENSION IS PROVIDED "CLASS B" IF: LAP SPLICES DO NOT MEET CLASS A REQUIREMENTS						

CONCRETE ANCHORS SHALL BE EITHER HILTI HIT-RE 500-V3 INJECTABLE MORTAR, SIMPSON STRONG-TIE SET-XP ANCHORING ADHESIVE, OR POWERS PE1000+ ADHESIVE ANCHORS AS SPECIFIED. WHERE SIZE IS CALLED OUT ON THE DRAWINGS, PROVIDE MINIMUM EMBEDMENT DEPTHS AS SHOWN ON THE FOLLOWING TABLES. PROVIDE MINIMUM EDGE DISTANCES AND SPACING AS SHOWN ON THE FOLLOWING TABLES UNLESS SPECIFICALLY DETAILED OTHERWISE. SPECIAL INSPECTION REQUIRED.

INSTALL ANCHORS IN STRICT ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS.

NOTIFY OWNER 48 HOURS IN ADVANCE OF INSTALLATION OF ALL ANCHORS.

WHERE SIZE IS NOT CALLED OUT, ANCHOR SHALL BE SELECTED BASED ON DESIGN LOADS. IF THE MINIMUM EDGE DISTANCE AND/OR MINIMUM SPACING CAN NOT BE ACHIEVED, REFER TO PRODUCT INFORMATION FOR REDUCTION IN ALLOWABLE LOADS.

CONCRETE ANCHORS HILTI HIT-RE 500-V3, SIMPSON STRONG-TIE SET-XP & POWERS PE1000+					
DIA. OF ROD (INCHES) OR REBAR SIZE NO.	MIN. EDGE DISTANCE (INCHES)	MIN. EMBEDMENT (INCHES)	MIN. ANCHOR SPACING (INCHES)	ALLOWABLE LOAD BASED ON BOND STRENGTH (POUNDS)	
				TENSION	SHEAR
1/2	2-1/2	2-3/4	2-1/2	1,027	2,210
5/8	3-1/8	3-1/8	3-1/8	1,312	2,827
3/4	3-3/4	3-1/2	3-3/4	1,556	3,351
7/8	4-3/8	3-1/2	4-3/8	1,556	3,351
#4	2-1/2	4-1/2	2-1/2	1,520	3,618
#5	3-1/8	5-5/8	3-1/8	1,775	5,494
#6	3-3/4	6-3/4	3-3/4	2,225	7,570
#7	4-3/8	7-7/8	4-3/8	2,440	9,428
#8	5	9	5	4,520	11,507

CONCRETE ANCHOR




DEFERRED SUBMITTALS:  
THE FOLLOWING ITEMS HAVE BEEN DEFERRED FOR SUBMITTAL TO THE BUILDING OFFICIAL UNTIL AFTER ISSUANCE OF THE BUILDING PERMIT:

- PREFABRICATED METAL-PLATE-CONNECTED WOOD TRUSSES  
- MECHANICAL PIPING SUPPORTS AND LATERAL BRACING  
- ANCHORAGE OF ELECTRICAL EQUIPMENT

WOOD

- W1. FRAMING LUMBER  
A. STUDS: HEM FIR STUD GRADE  
B. HEADERS: HEM FIR #2 OR BETTER  
C. RAFTERS: HEM FIR #2 OR BETTER  
W2. FASTENERS IN TREATED LUMBER: HOT-DIPPED GALVANIZED



SIGNED: 04/13/2023



SIGNED: 04/13/2023

PUBLIC UTILITY DISTRICT NO. 1 OF WHATCOM COUNTY

D STATION - FLOW AND CONTROL

IMPROVEMENTS

STRUCTURAL DETAILS I


Public Utility  
DISTRICT No. 1  
of Whatcom County

ENGINEER: OMP	REVISIONS	NO.	DATE	DESCRIPTION	BY	REVIEW
SWF DATE: Apr 13, 2023	JOB NO.: 21-0163	CLIENT: WPUD	FILENAME: DSTA-D-STRP.DWG	REVISIONS		
REVISED: DWG						

SCALE: SHOWN




DRAWING IS FULL SCALE WHEN BAR MEASURES 2"



200  
S01







NOT TO SCALE



200  
S01

NOT TO SCALE




1. ANCHOR BOLTS MUST BE PLACED WITHIN 12" OF EACH WALL CORNER AND ALL SILL PLATE SPLICES AT A MINIMUM 3 1/2" FROM THE EDGE.
2. MAXIMUM SPACING OF BOLTS IS 6'- 0". ADJUST SPACING SO THERE ARE A MINIMUM OF FOUR ANCHORS ON THE LONG SIDE AND TWO ANCHORS ON THE SHORT SIDE OF THE BUILDING.
3. BOLTS MUST BE 1/2" DIAMETER MINIMUM SIZE WITH WASHERS.
4. ALTERNATE ANCHOR BOLTS AND ANCHOR STRAPS MAY BE USED AND MUST BE INSTALLED PER MANUFACTURER'S INSTRUCTIONS AND MAY REQUIRE ENGINEER'S APPROVAL.

NOT TO SCALE

## REVISIONS

- 
- Technical drawing of a sump pump assembly, showing various components and dimensions. The drawing includes the following labels and dimensions:
- GROUT VAULT FLOOR TO SLOPE TOWARDS SUMP PUMP
  - 18" FLOW METER PER SPECIFICATIONS DIVISION 15.53.03
  - SEE DWG NO. C03 FOR SUMP PIPE CONTINUATION.
  - SUMP PUMP PER SPECIFICATIONS DIVISION 11.12.10
  - GRATING PER MANUFACTURER
  - 18" DI DISMANTLING JOINT (FLxFL)
  - 18" DI SPOOL (FLxFL), LENGTH 2'-0"
  - 18"x16" REDUCER (FLxFL), TYP. OF 2
  - 16" DI BUTTERFLY VALVE (FLxFL) WITH SHARKTOOTH CONTROL CARTRIDGE AND ELECTRIC ACTUATOR
  - APPROX. 2'-0"x2'-6" OPENING IN MOLDED FRP GRATING
  - THRUST BLOCK
  - 18" PIPE PER DWG NO. C03
  - APPROX. 6 7/8"
  - APPROX. 1'-2 3/8"
  - APPROX. 7 1/2"
  - APPROX. 11 3/8"
  - REMOVABLE APPROX. 3'-0"x3'-6" MOLDED FRP GRATING SECTION
  - PROVIDE INTERIOR LINK SEAL AND EXTERIOR WATERTIGHT GROUT PER PIPE PENETRATION DETAIL ON DWG NO. C04, TYPICAL ALL PENETRATIONS.
  - REMOVABLE APPROX. 2'-0"x3'-0" MOLDED FRP GRATING SECTION
  - 11"
  - NO. C03
  - CASTLE PRECAST 612-LA DIMENSIONS 12'-0"x6'-0") WITH INTEGRAL FOOTING BY THE CONTRACTOR.
  - 100 C04



**101**  
C04

PIPE SUPPORTS. LOCATIONS ARE CONCEPTUAL, CONTRACTOR TO ADJUST AND ADD PIPE SUPPORTS AS NECESSARY TO FULLY SUPPORT PIPING.

**A-A**  
M01

**METER VAULT SECTION**  
1/2" = 1'-0"

CONTRACTOR SUBMITTED AND DESIGNED MOLDED FRP GRATING WITH REMOVABLE SECTIONS TO REMOVE FLOW METER AND CONTROL VALVE

Gauge and Pressure Transmitter Assembly (300 M01)

STRONGWELL FIBERGLASS STANDARD LADDER WITH EXTENDED LADDER RAIL OR APPROVED EQUAL. PROVIDE LADDER SUPPORTS AS REQUIRED BY THE MANUFACTURER.

SURFACE PER PLAN

STRUCTURAL BACKFILL

CONCRETE VAULT, PROVIDE RISERS AS NECESSARY TO ACHIEVE TOP OF VAULT ELEVATION AND REQUIRED CLEARANCE BELOW PIPING.

PROVIDE BENTONITE WATER STOP BETWEEN VAULT SECTIONS

12"

#5 BARS AT 8" O.C., EACH WAY, EACH FACE, TYP.

18" DI WALL RING THRUST COLLAR, TYP.

1'-9"

12" MIN.

CONCRETE THRUST BLOCK

(2) HORIZONTAL #7 @ 4" O.C., EACH FACE, ABOVE AND BELOW PIPE, MAINTAIN 2" CLEARANCE TO PIPE AND THRUST RING.

#5x13" CONCRETE ANCHORS @ 18" O.C. VERT, 24" O.C. HORZ. EMBED 3" INTO VAULT WALL

(2) VERTICAL #5, EACH FACE, EACH SIDE OF THRUST RING, MAINTAIN 2" CLEARANCE TO PIPE AND THRUST RING.

INTEGRAL CONCRETE VAULT FOOTING, SIZE DETERMINED BY VAULT MANUFACTURER REFER TO METER VAULT BUOYANCY NOTES ON THIS SHEET.

PROVIDE 12" OF CRUSHED SURFACING BASE COURSE COMPACTED TO FIRM AND UNYIELDING CONDITION

NATIVE SOIL PROOF ROLL IN PRESENCE OF ENGINEER

NOTE: THRUST BLOCK WIDTH TO MATCH EXTERIOR VAULT WALL WIDTH.

2" RETURN BEND WITH 2" BRONZE BEEHIVE STRAINER

2" HDG PIPE, FIELD LOCATE.

18"

TRANSITION COUPLING

18" MIN. COVER

2" 90° BEND HDG


PVC DISCHARGE PIPE LENGTH AS REQUIRED

SEE DWG NO. C03 FOR SUMP PIPE CONTINUATION.

302  
C03

**GOOSE NECK DISCHARGE DETAIL**

NOT TO SCALE




1 EXISTING MECHANICAL LAYOUT



2 EXISTING MECHANICAL LAYOUT

TEMPORARILY REMOVE EQUIPMENT AND FITTINGS. REPLACE ONCE NEW PIPE AND SADDLE TAP ARE INSTALLED.

NOTE: DO NOT DISTURB EXISTING FITTINGS UNLESS OTHERWISE NOTED ON THESE PLANS.



MECHANICAL PLAN VIEW

1/2" = 1'-0"

**PUBLIC UTILITY DISTRICT NO. 1 OF WHATCOM COUNTY**  
**D STATION - FLOW AND CONTROL IMPROVEMENTS**

**D STATION MECHANICAL IMPROVEMENTS**

ENGINEER: OMP	DATE: Apr 13, 2023	CLIENT: WPUD	LOG NO.: 21-0163	REVISIONS	NO.	DATE	DESCRIPTION	BY	REVIEW
REVIEWED: DWB	PLOT DATE: Apr 13, 2023	FILE NAME: DSTA-D-MECH01.DWG							

SCALE: SHOWN

0"1"2"


DRAWING IS FULL SCALE WHEN BAR MEASURES 2"

DWG NO.: M02

SHEET NO.: 12

20





ELECTRICAL NOTES	
1	1. STUB-UP PROPOSED SPARE CONDUIT INSIDE BUILDING.
XX	2. SEE DWG NO. E07 FOR CONDUIT AND CONDUCTOR SCHEDULE.





SIGNED: 04/13/2023

PUBLIC UTILITY DISTRICT NO. 1 OF WHATCOM COUNTY

**D STATION - FLOW AND CONTROL IMPROVEMENTS**

PUBLIC UTILITY DISTRICT No. 1 of Whatcom County

**ELECTRICAL SITE PLAN**

REVISIONS		NO.		DATE	DESCRIPTION	BY	REVIEW

ENGINEER: BPC  
REVIEWED: MWB

DATE: Apr 13, 2023  
PLOT DATE: Apr 13, 2023

CLIENT: WPUD  
FILENAME: DSTA-D-ELEC02.DWG

JOB NO.: 21-0163

SCALE: SHOWN


0" 1" 2"

DRAWING IS FULL SCALE WHEN BAR MEASURES 2"

DWG NO.: E02

SHEET NO.: 14


20



UPPER METER VAULT BUILDING  
ELECTRICAL PLAN  
1/2" = 1'-0"





ELECTRICAL NOTES	
1	1. GROUND ROD PER N.E.C. (TYPICAL). USE EXOTHERMIC WELD CONNECTION AT THE GROUND ROD. SEE DWG NO. E08 FOR DETAIL. LOCATE GROUND RODS 2' MINIMUM FROM BUILDING FOUNDATION.
2	2. BOND GROUND SYSTEM TO WATER PIPING IN VAULT.
XX	3. SEE DWG NO. E07 FOR CONDUIT AND CONDUCTOR SCHEDULE.
X	4. SEE DWG NO. E07 FOR ELECTRICAL EQUIPMENT SCHEDULE.



LOWER METER VAULT BUILDING  
ELECTRICAL PLAN  
1/2" = 1'-0"





SIGNED: 04/13/2023


PUBLIC UTILITY DISTRICT NO. 1 OF WHATCOM COUNTY

D STATION - FLOW AND CONTROL IMPROVEMENTS

ELECTRICAL PLAN I

ENGINEER: BPC	DATE: Apr 13, 2023	CLIENT: WPUD	JOB NO.: 21-0163	REVISIONS	NO.	DATE	DESCRIPTION	BY	REVIEW
REVIEWED: MWB	PLOT DATE: Apr 13, 2023	FILE NAME: DSTA-DELEC03.DWG							

SCALE: SHOWN





DRAWING IS FULL SCALE WHEN BAR MEASURES 2'

DWG NO.: E03

SHEET NO.: 15

20



SIGNED: 04/13/2023

## D STATION - FLOW AND CONTROL IMPROVEMENTS

DISTRICT No. 1  
— of Whitcomb County —

# ELECTRICAL PLAN II

[illegible]




D STATION INTERIOR 1  
NO SCALE



D STATION INTERIOR 2  
NO SCALE



D STATION INTERIOR 3  
NO SCALE



D STATION INTERIOR 4  
NO SCALE

ELECTRICAL NOTES	
XX	1. SEE DWG NO. E07 FOR CONDUIT AND CONDUCTOR SCHEDULE.



PUBLIC UTILITY DISTRICT NO. 1 OF WHATCOM COUNTY  
D STATION - FLOW AND CONTROL IMPROVEMENTS  
ELECTRICAL PLAN III

REVISIONS		NO.	DATE	DESCRIPTION	BY	REVIEW

CONNECT PROPOSED  
— DIGITAL OUTPUT CIRCUITS  
TO SPARE OUTPUTS

NO SCALE


NO SCALE




NO SCALE

NO SCALE







GROUND TEE DETAIL  
NO SCALE



GROUND REBAR DETAIL  
NO SCALE




GROUND TEE DETAIL  
NO SCALE



GROUNDING CROSS DETAIL  
NO SCALE


STUB CONDUIT UP PAST  
FINISHED FLOOR ELEVATION,  
1" MINIMUM FROM THE PUMP  
STATION BUILDING WALL,  
AND TAPE TO SEAL.  
CONTRACTOR SHALL  
PROVIDE 3/16" NYLON PULL  
CORD.




CONDUIT STUB-UP DETAIL  
NOT TO SCALE

ELECTRICAL NOTES


1. GROUND ROD PER N.E.C. (TYPICAL). SEE THIS SHEET FOR DETAIL.
2. SEE DWG NO. E07 FOR ELECTRICAL EQUIPMENT SCHEDULE.



GROUNDING  
NO SCALE




GROUND ROD DETAIL  
NOT TO SCALE



TYPICAL ELECTRICAL TRENCH DETAIL  
NOT TO SCALE

NOTE: BURY DEPTH OF CONDUIT AND HORIZONTAL SPACING SHALL  
BE CONFIRMED WITH SERVING UTILITY BEFORE CONSTRUCTION.



FLOOD SWITCH DETAIL  
NOT TO SCALE



SIGNED: 04/13/2023

PUBLIC UTILITY DISTRICT NO. 1 OF WHATCOM COUNTY  
D STATION - FLOW AND CONTROL  
IMPROVEMENTS

ELECTRICAL DETAILS

NO.	DATE	DESCRIPTION	BY	REVIEW